



### Technical data

Material	
Backing	Special PP fleece
Adhesive	Water-resistant SOLID adhesive
Release film	Silicone-coated paper

  

Property	Regulation	Value
Colour		Dark blue
Thickness	EN 1849-2	0.50 +-0.05 mm
Can be plastered over		Yes
Application temperature		Above -10 °C
Temperature resistance		Permanent -50 °C to +90 °C
Storage		Cool and dry
Passive House Certification	Passivhaus Institut	phA

### Areas of application

TESCON® VANA airtight sealing tape is an essential component of all air barrier systems. It is compatible with membranes, underlays, as well as timber products, fibre cement, concrete & masonry. TESCO® VANA is airtight and vapour permeable. It is flexible, easy to cut, and has a simple-to remove release paper, ensuring maximum productivity during installation. TESCO® VANA provides an airtight adhesive seal to the substrate, forming excellent seals under all application conditions.

### Supply forms

Art. no.	Length	Width	Release film splits	Weight	Sales unit	Container	GTIN
12185	30 m	60 mm	No split	0.7 kg	10	480	4026639121851
11365	30 m	60 mm	No split	14.5 kg	1	24	4026639113658

### Advantages

- ✓ Long-term durability (tested for 100-year adhesion)
- ✓ Flexible to account for building movement
- ✓ Outstanding adhesion on cold surfaces
- ✓ Thin, highly pliable and easily formed into corners and shapes
- ✓ Airtight connection for the life of the building

### General conditions

#### IMPORTANT INFORMATION

- Long-term durability (tested for 100-year adhesion).
- Thin, highly pliable and easily formed into corners and shapes.
- Outstanding adhesion in cold conditions.
- Can be used to seal penetrations in INTELLO®.

#### PRODUCT DESCRIPTION

TESCON® VANA is a multi-purpose adhesive tape which forms an essential part of your air barrier system. Made from polypropylene with acrylate, it has excellent workability and adhesion for secure and permanent airtight seal of overlaps between INTELLO®, joints between membranes, and smooth, non-mineral surfaces. It is also suitable for sealing joints between wood based materials.

#### WEATHER EXPOSURE

This product is not designed for external use but will handle temporary direct exposure to UV and still fulfil the intended use for air control. Envelope and reveal details should be detailed to prevent direct sunlight from reaching the TESCO® VANA in service.

#### APPLICATION NOTES

This product should be applied using the PRESSFIX tool to activate the pressure-sensitive adhesive and guarantee a long-term durable seal.



© 2026 Pro Clima New Zealand. All rights reserved. The trademarks in this document are registered to Pro Clima or one or more of its affiliates.

The information provided in this document is based on practical experience and current knowledge and was correct at the time of publication. Pro Clima reserves the right to change technical details as developments occur and improvements are made to our products.

Pro Clima recommends reviewing the latest technical data on the [www.proclima.co.nz](http://www.proclima.co.nz) website to ensure the most current document version.

**PRO CLIMA NEW ZEALAND**  
Upper North Island: 09 892 9900  
Lower North Island: 04 589 8460  
South Island: 03 327 4925  
Technical: [support@proclima.co.nz](mailto:support@proclima.co.nz)  
General: [welcome@proclima.co.nz](mailto:welcome@proclima.co.nz)  
0800 PRO CLIMA (776 254)